



Turbine Wheel Flowmeter / Monitor

for liquids



measuring
•
monitoring
•
analysing

DRS



Model:
DRS-...Z

- Measuring range: 2 - 40 l/min water
- Measuring accuracy: $\pm 1.5\%$ of full scale
- p_{\max} : 200 bar; t_{\max} : 80 °C (optional 150 °C)
- Viscosity range: low viscous
- Connection:
G 1/2 female/male thread,
G 3/4 male/male thread
3/4" NPT male/male thread
- Material:
PPO/PEI/brass/stainless steel
- Output:
pulses, 0 - 20, 4 - 20 mA,
Switching output NPN



Model:
DRS-...0
DRS-...F5...



Model:
DRS-...C3



KOBOLD companies worldwide:

ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com

Application

KOBOLD model DRS flowmeters are used for measuring and monitoring liquids. Due to its compact construction the mini turbine is suitable for use with machines with minimum available space.

Application Examples

Beverage industry, devices for use in automatic beverage retail systems, washing machines, vehicles, farm equipment, developing machines in the photographic and printed-circuit board industries.

Working Principle

The flowmeter operates on the turbine wheel principle. The liquid first flows through a laminar flow element to eliminate turbulence and to route the flow stream to the turbine wheel. The turbine wheel then starts to rotate. This rotary motion is sensed non-contacting by magnets embedded in the turbine wheel and converted to a frequency signal. The frequency is proportional to the flow velocity.

Frequency divider, analogue output or compact electronics with LED display and limit contacts are available as options. An integrated temperature sensor for simultaneous measuring of flow rate and temperature are available as an additional option. The vane is sapphire-supported: this ensures a high degree of linearity and long service life.





Model Summary

- **DRS-0...K000, DRS-0...S000**
OEM version (without CE mark)
direct output from Hall-sensor signal
for DRS-K000 no optional temperature sensor available
DRS-0...S000 up to 150 °C medium temperature
- **DRS-...F300**
Pulse output
- **DRS-...F390**
Pulse output with adapted frequency
Factor 0.25...2
- **DRS-...L...**
Analogue output 0(4)-20 mA / 3-wire
- **DRS-...C30...**
With compact electronics, 3-digit LED display,
limit contacts, no optional temperature sensor available
- **DRS-...C34...**
With compact electronics
3-digit LED display, limit contact, analogue output
no optional temperature sensor available
- **DRS-...Z...**
With pointer indicator and analogue output
no optional temperature sensor available

Technical Details

Measuring range:	2 - 40 l/min water
Sensor pulse output:	384 Hz at 40 l/min metal sensor (DRS-150; DRS-250) 352 Hz at 40 l/min plastic sensor (DRS-350)
Max. operating pressure:	200 bar (DRS-150; DRS-250) 16 bar (DRS-350)
Temperature:	-20... +80 °C (medium) -20... +100 °C (bearing) -20... +150 °C (medium with DRS-...S)
Measuring accuracy:	±1,5% of full scale ±5% of full scale (DRS-...K0000)
Linearity:	±0,5% of full scale
Repeatability:	±0,1% of full scale
Electrical connection:	plug connector M12x1 1,5 m cable (DRS-0 only) 2 m cable (DRS-...F5 only) 1,5 m silicone cable (DRS-...S)
Protection:	IP 65 (plug connector), IP 66 (cable)

Weight (sensor and electronics)

Sensor:	approx. 80 g (DRS-...350) approx. 550 g (DRS-...150; DRS-...250)
Electronics:	approx. 60 g (DRS-...K.; DRS-...F.; DRS-...L3...) approx. 100 g (DRS-...L442) approx. 450 g (DRS-...Z...) approx. 650 g (DRS-...C...)

Electrical Data

DRS-0...K0000, DRS-...S000

Supply:	6...28 V _{DC}
Output pulse:	rectangular pulse signal, open collector NPN, max. 10 mA

DRS-...F300; DRS-...F500

Supply:	12-28 V _{DC}
Power consumption:	10 mA
Pulse output:	PNP, open collector, max. 20 mA
Option:	Pt 100, 3-wire

DRS-...F390

Supply:	24 V _{DC} ± 20 %
Power consumption:	15 mA
Pulse output:	PNP, open collector, max. 20 mA
Factor:	1...1/128 set at the factory
Option:	Pt 100, 2-wire
Response time:	t ₉₀ = 100 s

DRS-...L...

Supply:	24 V _{DC} ± 20 %
Output:	0(4)-20 mA, 3-wire or 2-wire
Max. load:	500 Ω
Option:	Pt 100 (2-wire)
Response time:	t ₉₀ = 100 s

DRS-...C30...

Compact electronics	
Display:	3-digit LED
Switching outputs:	2 semiconductor PNP or NPN, set at the factory
Contact operation:	N/C / N/O contact frequency programmable
Setting:	with 2 buttons
Supply:	24 V _{DC} ±20%, 3-wire
Electrical connection:	plug connector M12x1

DRS-...C34...

Compact electronics	
Display:	3-digit LED
Analogue output:	(0)4...20 mA adjustable
Switching outputs:	1 semiconductor PNP or NPN, set at the factory
Contact operation:	N/C / N/O contact / frequency programmable
Setting:	with 2 buttons
Supply:	24 V _{DC} ±20%, 3-wire
Power consumption:	approx. 100 mA
Electrical connection:	plug connector M12x1

DRS-...Z...

Pointer indicator with analogue output	
Housing:	aluminium
Display:	moving-coil instrument, 240° display
Power supply:	24 V _{DC} ±20%
Output:	0-20 mA or 4-20 mA, 3-wire
Max. load:	250 Ω
Electrical connection:	plug connector M12x1


Materials

Housing:	PPO, brass or stainless steel 1.4301
Turbine:	PEI
Magnets:	ceramic
Axle:	hard metal
Bearing:	sapphire
Seal:	NBR (others on request) FKM (DRS-0...S000)

Electrical Connection

DRS-...F., DRS-...L3... (3-wire without Pt 100)

Plug




Cable

brown: +Vs
blue: GND
black: Signal

DRS-...F., DRS-...L3... (3-wire with Pt 100)


Plug




Cable

brown: +Vs
blue: GND
black: signal
white: Pt 100 2-wire
grey: Pt 100 2-wire


DRS-...L342 (2-wire)




DRS-...Z...




Pressure loss




Frequency diagram (DRS-*150, DRS-*250)



DRS-...L442...



DRS-...C3...





Order Details (example: DRS-9350 I4 L303 0)

Material sensor housing	Model	Connection	Evaluating electronics	Option
Brass	DRS-9150	I4 = G 1/2 female thread G4 = G 1/2 female/male thread N5 = 3/4" NPT male thread G5 = G 3/4 male thread	Frequency output F300 = plug connector M12x1, PNP F320 = plug connector M12x1, PNP, divider 1:2 F340 = plug connector M12x1, PNP, divider 1:4 F390 = plug connector M12x1, PNP, divider 1...1/128 adjusted F500 = 2 m PVC cable, PNP Analogue output L303 = plug connector M12x1, 0-20 mA, 3-wire L342 = plug connector M12x1, 4-20 mA, 2-wire L343 = plug connector M12x1, 4-20 mA, 3-wire L442 = plug connector DIN 43 650, 4-20 mA, 2-wire Compact electronics¹⁾ C30M = LED display, 2 x NPN switching output, plug connector M12x1 C30R = LED display, 2 x PNP switching output, plug connector M12x1 C34N = LED display, 4-20 mA, 1 NPN switching output, plug connector M12x1 C34P = LED display, 4-20 mA, 1 PNP switching output, plug connector M12x1 Pointer indication, 240^{o1)} Z300 = pointer indication, 0-20 mA, plug connector M12x1 Z340 = pointer indication, 4-20 mA, plug connector M12x1	0 = without P = Pt 100 ²⁾ Y = special model
Stainless steel	DRS-9250			
Plastic (PPO)	DRS-9350			

¹⁾ Please specify flow direction in writing.

²⁾ For option F3/F5 and L3x3 only, brass or stainless steel version

Plug-on Display

for model DRS-...L442 (with 4-20 mA output and DIN plug connector)

Description	Order number
4-digit LED, connector DIN 43650, 2-wire, supply through analogue output	AUF-1000
as above however with additional open collector output	AUF-1001



Order Details OEM Version (example: DRS-0350 I4 K0000)

Material sensor housing	Model	Connection	Evaluating electronics
Brass	DRS-0150	I4 = G 1/2 female thread G4 = G 1/2 female/male thread N5 = 3/4" NPT male thread G5 = G 3/4 male thread	Frequency output K0000 = 1.5 m PVC cable, NPN, OEM without CE S0000 = 1.5 m silicone cable, NPN, OEM without CE, max. 150 °C (not for DRS-0350) S000P = 1.5 m silicone cable, NPN, OEM without CE, Pt 100, max. 150 °C (not for DRS-0350)
Stainless steel	DRS-0250		
Plastic (PPO)	DRS-0350		



Turbine Wheel Flowmeter/Monitor Model DRS

Dimensions [mm]

