



Viscosity-Compensated Plastic Flow Meters and Switches

for liquids



measuring
•
monitoring
•
analysing

VKP



- Measuring range:
2 - 20 ... 20 - 100 l/min water
1 - 18 ... 10 - 75 l/min oil
- Accurac: $\pm 5\%$ of full scale
- p_{\max} : 16 bar; t_{\max} : 120 °C
- Connection:
G1, 1" NPT
PVC glue-in connection,
inserts G $\frac{1}{2}$, G $\frac{3}{4}$
soldering connection 18 mm,
22 mm
- Material: polysulfone



S2



KOBOLD companies worldwide:


ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com

Description

The KOBOLD plastic flow meters model VKP operate on a special suspended float principle with cylindrical measuring tube and spring-loaded float with orifice. The float in model VKP-3... has slots moulded on the outside, which protect the instrument from soiling by depositing dirt particles. The danger of the float jamming is thus considerably reduced and soiled liquids with a particle size up to 400 µm can be measured without difficulty. In model VKP-2... a sharp-edged orifice in the float renders the instrument less sensitive to changes in viscosity.

Dimensions



Technical Details

- Housing: Polysulfone
- Connections: G 1 male thread;
1" NPT male thread
inserts G 1/2, G 3/4
PVC glue-in connection,
soldering connection 18, 22 mm (Ms)
- Float: Polysulfone
- Spring: stainless steel, 1.4310
- Toothed ring: stainless steel, 1.4310
- Flat seal: for model VKP-1.../3... NBR
for model VKP-2... Klingerit Oilit
- Max. temperature: 120 °C
85 °C (with contact)
60 °C (with PVC connection)
- Max. pressure: 16 bar
- Accuracy: VKP-1...: ± 5 % of full scale
VKP-2...: ± 5 % of full scale
VKP-3...: ± 7 % of full scale
- Installation position: horizontal or vertical

Option (for VKP-1 and VKP-2 only)

- Contact components: 1 N/O or N/C contact, bistable
- Electr. connection: connector DIN 43 650
- Switch capacity: max. 40 W/VA,
max. 230 V_{AC/DC},
max. 2 A
(No single value is allowed to be exceeded)

Applications

- Lubrication circuits
- Domestic electrical installations
- Machine tools
- Solar energy systems
- Cooling circuits
- Welding machines
- Pumps

Order Details (Example: VKP-1020 R25 S)

Standard version		For viscous media		For soiled media (particle size max. 400 µm)		Connection	Contacts (not for VKP-3..)
Water [l/min]	Order no.	Oil at 100 cSt [l/min]	Order no.	Water [l/min]	Order no.		
2-20	VKP-1020...	1-18	VKP-2018...	7.5-32.5	VKP-3032...	..R25..= G 1 male (standard) ..N25..= 1" NPT male	0 = without S = N/O contact C = N/C contact
5-35	VKP-1035...	2-30	VKP-2030...	10-45	VKP-3045...	..L18..= soldering conn. 18 mm ..L22..= soldering conn. 22 mm	
5-50	VKP-1050...	5-45	VKP-2045...	15-70	VKP-3070...	..PVC..= PVC-glue-in conn. 20 mm ..IG1..= G 1/2 female, brass	
10-80	VKP-1080...	10-75	VKP-2075...	20-100	VKP-3100...	..IG2..= G 1/2 female, st. steel ..AG1..= G 1/2 male, brass	
20-100	VKP-1100...	-	-	-	-	..AG2..= G 1/2 male, st. steel ..AG3..= G 3/4 male, brass	
						..AG4..= G 3/4 male, st. steel	