



Gel-filled pH-combined Electrode



measuring
•
monitoring
•
analysing

APS-Z
COMPACT-LINE



- Measuring range pH 0... 12/0... 14
- KCl gel fill (0% silver ions)
- Salt distillate for longer life time
- Ceramic diaphragm
or
PTFE ring diaphragm
(for very soiled or oily media)
- Integrated Pt 100 optional
- Rated pressure up to 10 bar
(at +25 °C)
- Temperature range:
-5 °C... +80 °C
- High temperature glass electrodes:
-5... +135 °C
(with ceramic diaphragm)
- Discharge system Ag / AgCl
in as a cartridge



KOBOLD companies worldwide:


ARGENTINA, AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHILE, CHINA, COLOMBIA, CZECHIA, EGYPT, FRANCE, GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO, NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SINGAPORE, SPAIN, SWITZERLAND, TAIWAN, THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com


A1

Description

The standard combined electrode for general pH measurements is filled with KCl gel (0% silver ions) and contains a salt distillate, which ensures longer stability times. The discharge system Ag/AgCl has been designed as a cartridge. The combined electrode version with PTFE ring diaphragm is especially suitable for tough service conditions, for example, service in clarification plants or in oily and very soiled media. A temperature sensor Pt-100 can be integrated VP (Vario Pin) Pg 13.5 screw cap). The electrode can resist pressure up to 10 bar. Its dimensions are 120 x 12 mm (DIN 19 263).



Electrode with PTFE ring diaphragm



Electrode with ceramic diaphragm

Technical Details

Material: general-purpose glass/
high temperature glass

Diaphragm: ceramic, diameter 1 mm
PTFE, annular

pH-values: pH 0 ... 12 (general-purpose glass)
pH 0 ... 14 (high temperature glass)

Temperature range: -5 ... +80 °C (general-purpose glass)
-5 ... +135 °C (high temperature glass)

Pressure range: up to 10 bar (at +25 °C)

Length of shaft: 120 mm

Diameter: 12 mm

Threaded plug head: Pg 13.5

Minimum conductivity: 100 µS/cm

Connection cable APK-Z for pH electrodes model Model APS-Z

- For pH measurement with an electrode without temperature sensor, model APK-Z...K:
Low noise coaxial cable
Diameter: 5 mm in black
Thermostability: -25 ... +70 °C
Length: 5 m, 10 m



- For pH measurement with an electrode with temperature sensor, Model APK-Z...R:
Low noise coaxial cable with VP (Vario Pin)-cable socket (4 stranded cables and shielding)
Diameter: 5,5 mm in black
Thermostability: -30 ... +70 °C
Length: 5 m, 10 m

Order Details Connection cable

Model	Cable length	Cable type
APK-Z	5 = 5 m cable length	K = standard coaxial cable R = coaxial cable for electrodes with Pt100 VP (Vario Pin)-cable socket
	1 = 10 m cable length	

Order Details Combined Electrode (Example: APS-Z 1 N 1)

Model	Diaphragm	Temperature sensor	Device version
APS-Z	1 = ceramic diaphragm	N = without temperature sensor (N-screwed head conduit thread Pg 13.5) R = with temperature sensor VP (Vario Pin) Pg 13.5 screw cap	1 = general purpose glass 2 = high temperature glass -5 ... +135 °C
	2 = PTFE diaphragm		